

Technical Data Sheet

Woodgrain Hot Stamping Foils

EB... ACL (25%, 10%, 3% Gloss)

Product Description

EB Foils are specially formulated for use on medium density fiberboard, real wood, some grades of particleboard and hardboard. Decorative and functional, the EB Foils can be applied on flat surfaces, profiles and contour edges.

EB... ACL with colorless sizing is especially designed for high speed flooring applications.

The gauge of the base film is 19 µm.

The product is available in common slit rolls as well as in spools.

Features

One step decoration process.
Superior print quality.
Dry transfer process.
Durable finish.
Ease of application – no clean up, no curing or drying.
Stocking program
Available in a wide variety of colours and patterns.
Customer colour matching available.

Recommended Stamping Conditions

Condition	
Transfer temperature	165 – 230°C
Type of Roller	Silicone Rubber (Durometer 60 – 80)
Traversing speed	Up to 90 m / min with multiple rollers

Storage conditions on separate demand

NOTE: Instructions given herein are approximate and adjustment may be required in adapting materials for use in any specific application. The data presented is a result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made. Date 06/2020

CFC Europe GmbH

Rigistraße 20
73037 Göppingen
Germany
Phone +49 7161 8009 0
www.itwsf.com