

U7608FC CLEAR

DESCRIPTION:

Lacquered Polyester for printed HSF Labels or Overlays.

APPLICATIONS:

The production of multicoloured Heat Transfer Foils.

RESISTANCE PROPERTIES:

Foil for applications with high resistance properties.

CHARACTERISTICS:

• Color: Clear

Optical properties: Coating and polyester are clear and transparent.

• Carrier Gauge: 23μm

Release characteristics: Medium

Characteristics: Flexible coating for applications on slightly uneven surfaces

Print Receptivity: Foil surface generally receptive to overprinting by Silk,

Offset, Flexo or XEICON digital printing inks.

However the customer should check compatibility of his ink first.

GENERAL INFORMATION:

Standard roll length

and width: on request

Labeling: Rolls labeled with: material reference, batch number and roll length. Further

details upon request. Splices: Butt splice made with heat resistant blue tape.

Packaging: Rolls on 76mm core and packed on pallets with wrapping.

Storage: Avoid excessive heat and moisture. Do not store beside heater or in direct

sunlight. Recommended temp. 0°C- 35°C.

NOTE: Instructions given herein are approximate and adjustment may be required in adapting materials for use in any specific application.

The data presented is a result of careful and extensive research. However, since the actual conditions under which the materials may be used are beyond our control, no warranty of any kind, expressed or implied, concerning the use of the products is made.